

DS-PEA2 Series Box Panic Alarm Station

DS-PEA2 series box panic alarm station is designed with 2 MP HD camera and dual network ports. It supports scheduled turning on/off the alarm lamp, two-way audio. It helps to realize alarm aid the first time and provides more efficient service for building social stability. It is mainly applied to school, square, tourist attraction, hospital, supermarket gate, market, station, parking lot, etc.



Key Features

- Adopts embedded Linux operation system and high-performance embedded SOC processor
- Supports network adaptive and video and audio adaptive to realize low latency
- H.264, H.264 SVC and H.265 video compression standard, and G.711U and G.726 audio compression standard
- Wide dynamic range (WDR) and high light compensation (HLC)
- Multiple communication protocols: TCP/IP, SNMP, HIK-SIP, RTSP, and ONVIF
- Video collection and all-day monitoring with 2 MP HD IR camera
- Supports EHome and Hik-Connect service for public network transmission
- Two-way audio function with up to 5 m communication distance; build-in high sensitive microphone
- Audio extension with 3.5 mm standard audio interface
- Build-in loudspeaker and pickup with cracking voice prevention
- External audible and visual alarm
- Dual network ports



Specifications

Model	DS-PEA2 Series Box Panic Alarm Station	
System parameters	Processor	High-Performance Embedded SOC Processor
	Operation system	Embedded Linux Operation System
Build-in camera parameters	Camera	2 MP HD IR Camera, IR Distance \geq 10 m
	FOV	Horizontal: 128° Vertical: 75° Diagonal: 147°
	Day & night	IR Cut Filter
	Video compression standard	H.264, H.264 SVC, H.265
	Resolution	1920*1080@25fps
Audio parameters	Audio input	1-ch Built-in Omnidirectional Microphone, Pickup Distance: 5 m 1-ch 3.5 mm Audio Interface for External Audio Input
	Audio output	1-ch 3 W Build-in Loudspeaker 1-ch 3.5 mm Audio Interface for External Audio Output
	Audio compression standard	G.711 U/64Kbps, G.726 /16Kbps
	Audio quality	Noise Suppression and Echo Cancellation
Network parameters	Network protocol	TCP/IP, RTSP, SNMP, SIP, ONVIF
	Ethernet	10 M/100 M Self-adaptive Ethernet Port
	Public network transmission	EHome, EZVIZ
	Network encryption	Supports User Lock-in and Password Security Prompt
Alarm	One-touch alarm	Supported
	Tampering Alarm	Supported
Device interfaces	Ethernet port	2 RJ45 10 M/100 M Self-adaptive Ethernet Port
	IO Input	2
	IO Output	2
	Alarm lamp	1, Light Can be Configured Separately
	Siren	1, Sound Can be Configured Separately
	SD Card	Standard Micro SD card Slot, Supports Micro SD/SDHC/SDXC Card, Max. 128G
	PSTN	1-ch
General	Power supply	100-240 VAC
	Power consumption	\leq 24W
	Working temperature	-40 °C to +60 °C (-40 °F to 140 °F)
	Working humidity	10% to 90%
	Installation	Hold Hoop and Wall Mounting
	Dimensions	516.5 mm \times 327.7 mm \times 125 mm (20.33" \times 12.90" \times 4.92")

Available Models

DS-PEA2-21