



GCF-0342

Acoplador óptico 1310-1550 90/10, marca Nextlink

Características del producto:

| Parameter | 1x2 | | |
|--------------------------------|--------------------------|------------|------------|
| Operating Wavelength (nm) | 1310/1550 | | |
| Operating bandwidth (nm) | ±40 | | |
| Grade | P | A | |
| Insert Loss(dB)Coupling ratio: | 1/99 | ≤22.5/0.25 | ≤23.5/0.35 |
| | 2/98 | ≤18.8/0.3 | ≤19.5/0.4 |
| | 3/97 | ≤17.0/0.35 | ≤17.8/0.45 |
| | 5/95 | ≤14.6/0.4 | ≤15.5/0.5 |
| | 10/90 | ≤11.2/0.75 | ≤12.0/0.8 |
| | 20/80 | ≤7.9/1.3 | ≤8.4/1.4 |
| | 30/70 | ≤6.0/1.9 | ≤6.3/2.1 |
| | 40/60 | ≤4.7/2.7 | ≤4.9/2.9 |
| 50/50 | ≤3.6 | ≤3.8 | |
| Excess Loss(dB) | 0.07 | 0.1 | |
| PDL(dB) | ≤0.15 | ≤0.20 | |
| Return Loss(dB) | >50 | | |
| Directivity(dB) | ≥55 | | |
| Operating Temperature(°C) | -40~85 | | |
| Storage Temperature(°C) | -40~85 | | |
| Connector | SC, FC, LC or customized | | |

Notes: The values are all tested at +23°C without connectors.

