



Especificaciones de Cable RG-11 Quad Shield con mensajero

CATV Coaxial Cable(RG11T-60BV)

Construction

Item	Construction
Center Conductor	1.63± 0.01mm Copper/CCS
Dielectric	7.11± 0.05mm Foam PE
First Shield	Bonded Aluminum Foil
Second Shield	16*5*0.16± 0.005mm Al-Mag braiding 60% coverage
Third Shield	Aluminum Foil
Fourth Shield	16*5*0.16± 0.005mm Al-Mag braiding 60% coverage
Jacket	10.03± 0.10mm PVC
Steel	1.83 mm

Electrical Characteristics

Impedance(Ω)	75± 3
Capacitance(pF/Ft)	54± 3
Velocity of Propagation(%)	85.0
Return Loss	20dB min (5-2300Mhz)



Attenuation		
[@68° F. (20° C.)]		
Frequency (MHz)	Maximum (dB/100 ft.)	Maximum (dB/100 m)
5	0.38	1.25
55	0.96	3.15
187	1.75	5.74
250	2.05	6.72
300	2.25	7.38
400	2.60	8.53
450	2.75	9.02
500	2.90	9.51
550	3.04	9.97
600	3.18	10.43
750	3.65	11.97
865	3.98	13.05
1000	4.35	14.27