

WCB AND WCE WALL MOUNT CABINET

Part Number: WCB



Part Number: WCE



STANDARD

Comply with ANSI/EIARS-310-D, DIN41491; PART1, IEC297-2, DIN41494; PART7 and GB/T3047.2-92 standard. Compatible with 19 inch international, Metric and ETSI standard.

FEATURES

- Exquisite design and workmanship, and precise dimension increase the value of the projects.
- International popular smoky-gray stalinite front door.
- Easy to mount on wall, or put on floor with caster or feet.
- Loading capacity: 60kg.
- Top and bottom wiring channel could be closed.
- Detachable doors ensure operation in all direction.
- Surface finish: degreasing, pickling, phosphoric, water cleaning, and electrostatic powder coating .
- Comply with ROHS.
- Color: black or gray.
- Different accessories are available.

Part Number: WCC



MATERIALS

Produced by cold-rolled steel. Thickness of standard B-type square strip: 1.5 mm, other thickness: 1.2mm; Thickness of standard E-type square strip: 1.2mm, other thickness: 0.8 mm; smoky gray stalinite thickness: 5.00mm.

ORDER INFORMATION

Part No.	Capacity /U	Width/mm	Depth/mm	Height/mm	Carton measurement			Volume/CBM
					Width/M	Depth/M	Height/M	
WCB06-645-*#	6U	600	450	368	0.67	0.52	0.43	0.15
WCB09-645-*#	9U	600	450	501	0.67	0.52	0.56	0.20
WCB12-645-*#	12U	600	450	635	0.67	0.52	0.70	0.24
WCB15-645-*#	15U	600	450	769	0.67	0.52	0.83	0.29
WCB06-66-*#	6U	600	600	368	0.67	0.67	0.43	0.19
WCB09-66-*#	9U	600	600	501	0.67	0.67	0.56	0.25
WCB12-66-*#	12U	600	600	635	0.67	0.67	0.70	0.31
WCB15-66-*#	15U	600	600	769	0.67	0.67	0.83	0.37
WCE06-645-*#	6U	600	450	368	0.67	0.52	0.43	0.15
WCE09-645-*#	9U	600	450	501	0.67	0.52	0.56	0.20
WCE12-645-*#	12U	600	450	635	0.67	0.52	0.70	0.24
WCE06-66-*#	6U	600	600	368	0.67	0.67	0.43	0.19
WCE09-66-*#	9U	600	600	501	0.67	0.67	0.56	0.25
WCE12-66-*#	12U	600	600	635	0.67	0.67	0.70	0.31

REMARKS

\*=Front door #=Rear door

COLOR

☆ = Colors      A= Black (RAL9004)      B=Gray(RAL7044)